





REV	ECN NO.	APPD
A	HC-16-0124	ZO




RECOMMENDED P.C.B. LAYOUT

安装尺寸图



CIRCUIT DIAGRAM
回路图



规格 Specifications

额定负荷 Rating	DC 12V/20mA	
接触电阻 Contact Resistance	100mΩ max	
绝缘电阻 Insulation resistance	DC:100V 60S 100MΩ min	
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S	
操作力 Operation force	160±30gf	250±50gf
寿命试验 Operating Life	1,00,000 cycles	100,000 cycles
行程 Travels	0.20±0.1mm	

PRODUCT NO.: 1TS001G*****-CT

轻触开关
4x4系列
外形:
按钮颜色:
底座颜色:
盖板颜色:

材料:
0=初始材料
1=新增材料
依次增加

产品高度 (H):
130=1.30mm
160=1.60mm
170=1.70mm
200=1.70mm

初始颜色, 则不启用

操作力度:

手感:
0=常规(弹片)
1=大手感(弹片)
2=小手感(弹片)
3=特殊手感(弹片)

130=130gf
160=160gf
180=180gf
250=250gf

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
6	HOUSING	1	LCP	BLACK
5	TERMINAL	4	BRASS	Ag-plating
4	DOVE	1	SUS	Ag-plating
3	PE-FILE	1	0.05	YELLOW
2	COVER	1	SUS	PRIMARY
1	ACTUATOR	1	BRASS	YELLOW

X. ±	0.2	X' ±	3'	UNITS	MM
X ±	0.1	X' ±	2'	MATL	
.XX ±	0.05	.XX' ±	1'		
.XXX ±	0.03	.XXX' ±	0.5'	FINISH	

NAME(INTENDED USE)	4X4	HON YUAN
TACT SWITCH		HON YUAN PRECISION IND. CO.,LTD.
PART NO.(INTENDED USE)		SHENZHEN, CHINA.
1TS001G-****-***0		
APPD:	ZO 11/30/2016	DWG NO.:
CHKD:	M.H.LI 11/30/2016	1TS001G

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.	Q'TY	SCALE	SHEET	REV.
		10/1	1/1	A