




ACAD GENERATED DRAWING. DON'T CHANGE BY HAND.





CIRCUIT DIAGRAM
回路图



RECOMMENDED P.C.B. LAYOUT

安装尺寸图

规格 Specifications			
额定负荷 Rating	DC 12V/50mA		
接触电阻 Contact Resistance	100mΩ max.		
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.		
抗电强度 Dielectric strength	AC250V(50-60HZ) 60S min.		
操作力 Operation force	≤180±30gf	≤300±50gf	
寿命试验 Operating Life	50,000 cycles	30,000 cycles	
行程 Travels	0.25±0.1mm		



PRODUCT NO. : 1TS002*****-CT

- 轻触开关
- 3X6系列
- 外形:
- A=插脚
 - B=贴片
 - C=贴片带柱
 - E=贴片2.5高
 - K=贴片带柱8.8
 - L=贴片10.2
- 按钮颜色:
- 底座颜色:
- 盖板颜色:
- 操作力度:
- 130=130±20gf
 - 160=160±30gf
 - 180=180±30gf
 - 220=220±40gf
 - 250=250±50gf
 - 300=300±50gf
- 手感:
- 0=常规
 - 1=大手感
 - 2=小手感
 - 3=特殊手感
- 材质:
- 0=PA66
 - 1=LCF+PPA
 - 2=ICP
 - 3=PA66+PPA
 - 4=新增材质依次增加
- 产品高度(H):
- 430=4.3mm
 - 500=5.0mm
- 编织带 非编织带,不启用

3	ACTUATOR	1	PA66	WHITE
4	COVER	1	STAINLESS STEEL	NATURAL
3	DOME	1	STAINLESS STEEL	Ag-PLATED
2	HOUSING	1	PA66	WHITE
1	TERMINAL	1	BRASS	Ag-PLATED/0.2μm
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
X ± 0.3	X ± 3	UNITS	MM	
X ± 0.2	X ± 2	MAT'L		
.XX ± 0.1	.X ± 1	PART NO.(INTENDED USE)	HON YUAN HON YUAN PRECISION IND. CO.,LTD. SHENZHEN, CHINA, R.O.C.	
.XXX ± 0.05	.XXX ± 0.5	ITS002C***-****-****0	TITLE: PRODUCT DRAWING	
FINISH		APPD: ZO 2015/11/12	DWG NO.: 1TS002C	
QTTY		CHKD: M.H.Li 2015/11/12		
DR: WP.Lu 2015/11/11		<div><div><div><div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div></div></div><div></div></div><div>SCALE</div><div>SHEET</div><div>REV.</div><div>10/1</div><div>1/4</div><div>D</div></div>		

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. ANY REPRODUCTION, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.