


规格 Specifications

额定负荷 Rating	DC 12V/50mA	
接触电阻 Contact Resistance	100mΩ max.	
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.	
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.	
操作力 Operation force	160±30gf	250±50gf
寿命试验 Operating Life	100,000 cycles	70,000 cycles
行程 Travels	0.25±0.1mm	

RECOMMENDED P.C.B. LAYOUT

安装尺寸图



PRODUCT NO.: 1TS005A*****-CT

- 轻触开关
- 系列: 外形: 按钮颜色: 底座颜色: 盖板颜色: 操作力度: 初始颜色, 则不启用
- 材质: 0=初始材质 1=新增材质 依次增加
- 产品高度(H): 430=4.3mm 700=7.0mm
- 手感: 0=常规(薄片)
- 120=120gf 160=160gf 250=250gf
- 非编带 非编带, 不启用

5	COVER	1	Stainless Steel	NATURAL
4	ACTUATOR	1	PPA	BLACK
3	DOME	1	Phosphor Bronze/Ag	Ag-PLATED
2	TERMINAL	1	BRASS	Ag-PLATED
1	HOUSING	1	PPA	BLACK
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH

X. ± 0.3	X' ± 3'	UNITS	MM	NAME(INTENDED USE)	6X6	HON YUAN
X ± 0.2	X' ± 2'	MATL		TACT SWITCH		HON YUAN PRECISION IND. CO.,LTD.
.XX ± 0.1	.XX' ± 1'	FINISH		PART NO.(INTENDED USE)	1TS005A-*****-1	SHENZHEN, CHINA, R.O.C.
.XXX ± 0.05	.XXX' ± 0.5'			APPD:	ZO 2013/06/29	PRODUCT DRAWING
		Q'TY		CHKD:	M.H.LI 2013/06/29	DWG NO.: 1TS005A
				DR.Y.Y.Chen	2013/06/29	SCALE 10/1
						SHEET 2/2
						REV. A

REV	ECN NO.	APPD
A	HC-13-0018	PRJ0J0M