


RECOMMENDED P.C.B. LAYOUT

安装尺寸图

规格 Specifications			
额定负荷 Rating	DC 12V/50mA		
接触电阻 Contact Resistance	100mΩ max.		
绝缘电阻 Insulation resistance	DC100V 60S	100MΩ	min.
抗电强度 Dielectric strength	AC250V (50~60HZ) 60S min.		
操作力 Operation force	≤180±30gf	≥250±50gf	
寿命试验 Operating life	100,000cycles	100,000cycles	
行程 Travels	看左侧编码说明		



PRODUCT NO. : 1TS009\*\*\*\*\*-CT

- 轻触开关 TMRV系列
- 外形:
- A=弧盖弯脚
  - B=平盖弯脚
  - C=弧盖平脚
  - D=平盖平脚
- 按钮颜色:
- 底座颜色:
- 盖板颜色:
- 操作力度:
- 160=160±30gf
  - 180=180±30gf
  - 250=250±50gf
  - 260=260±50gf
  - 280=280±50gf
  - 300=300±50gf
- 手感:
- 0=常规
  - 1=大手感
  - 2=小手感
  - 3=特殊手感
- 材质:
- 0=LCP
  - 1=新增材质
  - 依次增加
- 产品高度 (H):
- 430=4.3mm (行程: 0.7±0.2mm)
  - 500=5.0mm (行程: 1.3±0.3mm)
- 编带 非编带, 不启用

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
5	COVER	1	LCP	BLACK
4	ACTUATOR	1	SILICONE	/
3	CONTACT	1	STAINLESS STEEL	Ag-PLATED
2	TERMINAL	2	BRASS	Ag-PLATED
1	HOUSING	1	LCP	BLACK

UNIT	MM	NAME(INTENDED USE)	HON YUAN
MAT'L		TMRV SERIES TACT SWITCH	HON YUAN PRECISION IND. CO.,LTD. SHENZHEN, CHINA, R.O.C.
FINISH		PART NO.(INTENDED USE)	TITLE: PRODUCT DRAWING
		1TS009B-****-***0	
APPD:	ZO 2015-11-10	DWG NO.:	1TS009B
CHKD:	LI 2015-11-10		
DRY.Y.Chen	2015-11-10		

Q'TY	SCALE	SHEET	REV.
	10/1	1/1	B