




规格 Specifications		
额定负荷 Rating	DC 12V/50mA	
接触电阻 Contact Resistance	500mΩ max.	
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.	
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.	
操作力 Operation force	160±20gf	240±30gf
寿命试验 Operating Life	300,000 cycles	
行程 Travels	0.12±0.05mm	



PRODUCT NO.: 1TS028A\*\*\*\*\*

其它:

CT=编带(非编带, 不启用)

轻触开关

2. 8X1.9系列

外形:

A=四脚

B=两脚

触点颜色:

底座颜色:

贴膜颜色:

操作力:

手感:

初始颜色

则不启用

产品高度(H):

050=0, 55mm

055=0, 55mm

060=0, 60mm

0=常规(弹片)

1=大手感(弹片)

2=小手感(弹片)

3=特殊手感(弹片)

材质:

0=初始材质

1=新增材质

依次增加

按点颜色:

底座颜色:


贴膜颜色:

操作力:

手感:

初始颜色

则不启用

	5	ACTUATOR	1	PA	BLACK	
	4	PI	1	FLIM	WHITE	
	3	DOVE	2	STAINLESS STEEL	Ag-PLATED	
	2	HOUSING	1	PA	BLACK	
	1	TERMINAL	2	PHOSPHOR BRONZE	Ag-PLATED	
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH		
ITEM P/N	PART NAME	Q'TY	MAT'L	FINISH	SPECIFICATION	REMARK
X. ± 0.2	X. ± 3'	UNITS		NAME(INTENDED USE)	HON YUAN HON YUAN PRECISION IND. CO.,LTD. SHENZHEN, CHINA, R.O.C.	
.X ± 0.1	.X' ± 2'	MM		2.8X1.9 SERIES TACT SWITCHES		
.XX ± 0.05	.XX' ± 1'	MAT'L		PART NO.(INTENDED USE)		
.XXX ± 0.03	.XXX' ± 0.5'	FINISH		1TS028A****-*****0	TITLE:	PRODUCT DRAWING
			APPD:	DWG NO.:	1TS028A	
			CHKD:			
		Q'TY	DR: WP.LU 12/18/2018			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.						
				SCALE	SHEET	REV.
				25/1	1/1	A