



REV	ECN NO.	APPD
A	HC160053	PRIOJOM


规格 Specifications

额定负荷 Rating	DC 12V/50mA	
接触电阻 Contact Resistance	100mΩ max.	
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.	
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.	
操作力 Operation force	≤180±30gf	250±50gf
寿命试验 Operating Life	100,000 cycles	50,000 cycles
行程 Travels	0.20±0.10mm	



RECOMMENDED P.C.B. LAYOUT

安装尺寸图



PRODUCT NO. : 1TS006\*\*\*\*\* - CT

轻触开关

4.5×4.5系列

外形:

按钮颜色:

底座颜色:

盖板颜色:

操作力度:

180=180gf

250=250gf

手感:

0=常规

1=大手感

2=小手感

3=特殊手感

材料:

0=初始材料

1=新增材料

依次增加

编带

非编带, 不启用

产品高度 (H):

380=3.80mm

500=5.00mm

650=6.50mm

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
5	COVER	1	Stainless Steel	/
4	ACTUATOR	1	PA46	BLACK
3	DOVE	1	Stainless Steel/Ag	Ag-PPLATING
2	TERMINAL	1	BRASS	Ag-PPLATING
1	HOUSING	1	PA46	BLACK

X. ± 0.3	X' ± 3'	UNITS	MM
.X ± 0.2	.X' ± 2'	MATL	
.XX ± 0.1	.XX' ± 1'	FINISH	
.XXX ± 0.05	.XXX' ± 0.5'		

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.	QTY	CHKD: M.H.Li 4/8/2016	DWG NO.: 1TS006A
		DR: Y.Y.Chen 4/8/2016	SCALE SHEET REV. 10/1 1/1 A