



REV	ECN NO.	APPD
A	HC-20-0014	PROJOM




规格 Specifications

额定负荷 Rating	DC 12V/50mA	
接触电阻Contact Resistance	100mΩ max.	
绝缘电阻Insulation resistance	DC100V 60S	100MΩ min.
抗电强度Dielectric strength	AC250V(50~60HZ) 60S min.	
操作力Operation force	160±30gf	250±50gf
寿命试验Operating life	100,000cycles	
行程Travels	0.15±0.1mm	



RECOMMENDED P.C.B. LAYOUT

安装尺寸图



CIRCUIT DIAGRAM
回路图

PRODUCT NO.: 1TS019B*****

轻触开关

4. 5X4.5系列

外形:

A=平脚

B=弯脚

贴点颜色:

底座颜色:

初始颜色

则不启用

操作力度:

160=160gf

250=250gf

290=290gf

手感:

0=常规(弹片)

1=大手感(弹片)

2=小手感(弹片)

3=特殊手感(弹片)

产产品高度(H):

0.55=0.55mm

材质:

0=初始材质

1=新增材质

依次增加

其它:

CT=编带(非编带,不启用)

其它:

其它:

其它:

其它:

其它:

其它:

其它:

其它:

其它:

其它:

其它:

其它:

其它:

4	FILM	1	PI	YELLOW
3	DOVE	1	STAINLESS STEEL	Ag-PLATED
2	HOUSING	1	LCP	BLACK
1	TERMINAL	1	PHOSPHOR BRONZE	Ag-PLATED
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
X. ± 0.2	X. ± 3'	UNITS	MM	
.X ± 0.1	.X' ± 2'	MATL		
.XX ± 0.05	.XX' ± 1'	FINISH		
.XXX ± 0.03	.XXX' ± 0.5'			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL REMAIN THEIR PROPERTY IF COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.				
QTY				
DR: Y.Y.Chen	2020-5-11			
CHKD: M.H.Li	2020-5-11			
APPD: ZO	2020-5-11			
PART NO.(INTENDED USE)	4.5X4.5 TACT SWITCH			
NAME(INTENDED USE)	1TS019B-****-0550			
TITLE:	PRODUCT DRAWING			
DWG NO.:	1TS019B			
SCALE	SHEET	REV.		
10/1	1/1	A		